DTF STATION

L2

Fume Extractor

Captures particulates at the source to maintain a **safer, more comfortable** print environment.



Cleaner, Safer Production.

Extraction at the source

Captures particulates where they are produced rather than after they have spread through the room.

Oil and smoke separation

A separation system handles oil mist and smoke before they reach the filter stage.

Compact

12" x 16" x 21" and 60 lb, so it saves space in a production environment.

Low-noise operation

Quiet enough that it does not make the workspace worse in a different way.

62W on a standard outlet

110V at 0.56A. Effectively free to run and no electrical work to install.

Support & Warranty

- **Lifetime** DTF Station tech support
- **1-year limited warranty** on non-consumable parts
- Compatible with DTF printers, ovens and shakers
- Easy-to-replace parts and accessories

See it run. Contact your DTF Station **dealer** or visit **dtfstation.com**.

Contact Us

sales@dtfstation.com

(562) 573-1117

dtfstation.com

@dtfstation

Dealer Locator

DTF STATION

Extraction At the Source.

Extraction, not purification.

The L2 captures particulates, oil mist and smoke at the source. It is a fume extractor, and that is deliberately how it is named. Treat it as source capture for a specific machine rather than as room air treatment.

Broad compatibility.

It works with a wide range of DTF printers, ovens and shakers, so it can move between machines as a shop's layout changes.

Cheap to run and maintain.

62W on standard 110V, low-noise operation, and easy-to-replace parts and accessories for simplified maintenance.



Support Every Step of the Way

Each machine comes with more than a warranty.

- **Full video library** — install, troubleshooting, maintenance
- Searchable **knowledge base** of written guides
- **Live ticketing** support via Discord
- **AI-powered triage bot** for instant first answers

Install & Facility

Dimensions (W x D x H)	12" x 16" x 21"
Weight	60 lb (27 kg)
Power Supply	110 V
Rated Current	0.56 A
Power Consumption	62 W

Specifications

Air Speed	15 m/s	**Maintenance**	Easy-replace parts
Separation	Oil and smoke	**Compatibility**	DTF printers, ovens, shakers
Noise	Low-noise operation		